

Listing and Amendments to the Claims

This listing of claims will replace the claims that were published in the PCT
Application:

Claims 1 through 10 are cancelled.

11. (new) Outside unit for receiving waves originating from a satellite, the unit comprising means of amplification and means of transposition using two transposition frequencies to transpose a satellite reception band to an intermediate frequency band of smaller size than the size of the reception band, wherein the two transposition frequencies are such that a part of the satellite reception band is transposed to the intermediate frequency band in an infradyne manner by using one of the transposition frequencies and another part of the satellite reception band is transposed to the intermediate frequency band in a supradyme manner by using the other of the transposition frequencies, and in that the two transposition frequencies are chosen so that there exists an intersection common to the two parts of the band of the satellite reception band which is transposed to the intermediate band with the aid of each of the two oscillators with a spectrum inverted on itself.

12. (new) Outside unit according to Claim 11, wherein one of the transposition frequencies is situated at a frequency below the bottom frequency of the satellite reception band from which is subtracted the bottom frequency of the intermediate band and in that the other of the frequencies is situated at a frequency above the upper frequency of the satellite reception band to which is added the base frequency of the intermediate band.

13. (new) Outside unit according to Claim 12, wherein one of the transposition frequencies is equal to 9.75 GHz and the other of the frequencies is equal to 13.7 GHz.

14. (new) Outside unit according to Claim 12, wherein the maximum spacing between the oscillation frequencies is fixed by the width of the reception band to which is added twice the bottom frequency of the intermediate band and to which is also added 81 MHz.

15. (new) Outside unit according to Claim 14, wherein one of the transposition frequencies is equal to 9.72 GHz and the other of the frequencies is equal to 13.73 GHz.

16. (new) Outside unit according to Claim 11, wherein the means of transposition comprises two oscillators which are alternatively supplied so as to have a transposition signal of fixed frequency chosen from among the two transposition frequencies .

17. (new) Method of receiving a radio signal originating from a satellite in a satellite reception band with the aid of an outside unit having means of amplification and means of transposition using two transposition frequencies to transpose a satellite reception band to an intermediate frequency band of smaller size than the size of the intermediate band, wherein the reception band is separated, for a given polarization, into at least four subbands of increasing frequencies and in that a part of the satellite reception band is transposed to the intermediate frequency band in an infradyne manner by using one of the transposition frequencies and another part of the satellite reception band is transposed to the intermediate frequency band in a supradyne manner by using the other of the transposition frequencies, two adjacent subbands are transposed with the aid of two different transposition frequencies.

18. (new) Method according to Claim 17, wherein one of the transposition frequencies is situated at a frequency below the bottom frequency of the satellite reception band from which is subtracted the bottom frequency of the intermediate band and in that the other of the frequencies is situated at a frequency above the upper frequency of the satellite reception band to which is added the base frequency of the intermediate band.

19. (new) Method according to Claim 18, wherein one of the transposition frequencies is equal to 9.75 GHz and the other of the frequencies is equal to 13.7 GHz.

20. (new) Method according to Claim 18, wherein the maximum spacing between the oscillation frequencies is fixed by the width of the reception band to which is added twice the bottom frequency of the intermediate band and to which is also added 81 MHz.

EXPRESS MAIL LABEL NO. EV 913276264 US
Customer No. 24498

PF040013

21. (new) Method according to Claim 20, wherein one of the transposition frequencies is equal to 9.72 GHz and the other of the frequencies is equal to 13.73 GHz.